

Operator for sliding gates up to 800 lbs weight and 25 ft length each.

Post mounted, appropriate for **high cycle residential and light commercial applications.**



Versatile: available in 7200ETL single version and 7200ETLDUAL dual gate version, Post mounted including an additional chassis with 38 ft. cable. Supplied with 35 ft #40 roller chain.

Solar compatible: optional 12 V battery (required) can be charged by either solar or AC power. The choice is yours!

Easily installable on most existing or new slide gates. The operator has practical adjustment of the limit switches and internal quick release system.

Both models use **the single/dual advanced 1050 circuit board** offering:

- LCD display for easy programming, diagnosing and troubleshooting;
- Innovative obstacle detection system;
- Plug-in receiver: up to 1,000 rolling-code transmitters;
- Smart management of the battery charging;
- Integrated 7 day timer;
- Master/slave management for two motors working together;
- Protection against electrical surges;
- Programmable inputs for external accessories.

Quality and durability to corrosion thanks to the housing, weather resistant NEMA 3R, powder coated black.

Code	Description	Approvals
7200ETL-1K	Operator 12 Vdc for slide gates up to 25 ft. and 800 lbs. each, single gate version. 1050 circuit board with enclosure	ETL
7200ETLDUAL-1K	Operator 12 Vdc for slide gates up to 25 ft. and 800 lbs. each, dual gate version. 1050 circuit board with enclosure	ETL

Technical Specifications

Code	7200ETL-1K	7200ETLDUAL-1K
Electrical data		
Power Supply (Vdc)	12-30	
Operation (Vdc)	12	
Absorption - standby (mA)	10	
Performance data		
Speed open (ft/s)	1	
Duty Cycle (cycles/hour)	Varies based on charging capacity	
Dimensions and general data		
Working Temp (°F Min/Max)	-40 ÷ +150	
Dimensions (inches)	21.5x21x11.5	